

LED poster

- ✓ **Pixel pitch:** Indoor P1.25/ P1.5/ P1.8/ P2.5
- ✓ **Pixel pitch:** Outdoor P3.33/ P4/ P5/ P6.66
- ✓ **Dimension:** customized
- ✓ **Brightness:** Indoor 0~700cd/m2
- ✓ **Brightness:** Outdoor >5000cd/m2
- ✓ **Control method:** 4G/WIFI control by mobile phone
computer/Ipad/Cloud



Product details & specifications

6 Posters, One Seamless Big Screen



Specifications	LED POSTER-B1.25	LED POSTER-B1.5	LED POSTER-B1.8	LED POSTER-B2.5
Pixel Pitch	1.25mm	1.53mm	1.88mm	2.5mm
Display Area	640mm×1920mm×59mm	640mm×1920mm×59mm	640mm×1920mm×59mm	640mm×1920mm×59mm
Frame Area	660mm×2022mm (with folding frame/wheels optional)	660mm×2022mm (with folding frame/wheels optional)	660mm×2022mm (with folding frame/wheels optional)	660mm×2022mm (with folding frame/wheels optional)
Physical Resolution	512×1536	416×1248	344×1032	256×768
GOB Protection	Optional	Optional	Optional	Optional
Multi-screen Spicing	Optional	Optional	Optional	Optional
Contrast Ratio	5000:1	5000:1	5000:1	5000:1
Brightness	0~700cd/m²	0~700cd/m²	0~700cd/m²	0~700cd/m²
Grey Scale	14bit	14bit	14bit	14bit
Refresh Rate	3840Hz	3840Hz	3840Hz	3840Hz
Viewing Angle	160°(H) / 140°(V)	160°(H) / 140°(V)	160°(H) / 140°(V)	160°(H) / 140°(V)
OS	Android 11	Android 11	Android 11	Android 11
Response Time	≤0.5ms (Typ)	≤0.5ms (Typ)	≤0.5ms (Typ)	≤0.5ms (Typ)
Audio Interface	Audio ×1	Audio ×1	Audio ×1	Audio ×1
Control Interface	RJ45 + WIFI + USB (Standard), 4G (Optional)	RJ45 + WIFI + USB (Standard), 4G (Optional)	RJ45 + WIFI + USB (Standard), 4G (Optional)	RJ45 + WIFI + USB (Standard), 4G (Optional)
Input Voltage	100-240V~50/60Hz			
Power Consumption	≤180W(avg)/≤600W(peak)	≤180W(avg)/≤600W(peak)	≤180W(avg)/≤600W(peak)	≤180W(avg)/≤600W(peak)
Weight	~50kg (with base wheels + brackets)	~50kg (with base wheels + brackets)	~50kg (with base wheels + brackets)	~50kg (with base wheels + brackets)
Operating Temp	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C
Operating Humidity	10%~65%RH	10%~65%RH	10%~65%RH	10%~65%RH